

# ISO 3601-1

ORINGONE COMPLETE VERSION

March 2020 release

CROSS SECTION		ORINGONE TOLERANCE APPLIED		STANDARD TOLERANCE	
mm	Inch	mm	Inch	mm	Inch
2,62	.103	± 0,08	± .003	± 0,08	± .003
3,00	.118	± 0,09	± .003	± 0,09	± .003
3,53	.139	± 0,10	± .004	± 0,10	± .004
4,00	.157	± 0,10	± .004	± 0,10	± .004
4,50	.177	± 0,10	± .004	± 0,10	± .004
5,00	.197	± 0,13	± .005	± 0,13	± .005
5,33	.210	± 0,13	± .005	± 0,13	± .005
5,50	.216	± 0,13	± .005	± 0,13	± .005
5,70	.224	± 0,15	± .006	± 0,13	± .005
6,00	.236	± 0,15	± .006	± 0,13	± .005
6,35	.250	± 0,15	± .006	± 0,15	± .006
6,50	.256	± 0,15	± .006	± 0,15	± .006
7,00	.276	± 0,15	± .006	± 0,15	± .006
7,10	.280	± 0,15	± .006	± 0,15	± .006
7,50	.295	± 0,15	± .006	± 0,15	± .006
8,00	.315	± 0,18	± .007	± 0,15	± .006
8,20	.323	± 0,18	± .007	± 0,15	± .006
8,40	.331	± 0,18	± .007	± 0,15	± .006
8,50	.334	± 0,18	± .007		
8,60	.339	± 0,18	± .007		
9,00	.354	± 0,20	± .008		
9,50	.375	± 0,20	± .008		
9,65	.380	± 0,20	± .008		
10,00	.394	± 0,20	± .008		
10,82	.425	± 0,20	± .008		
11,00	.433	± 0,20	± .008		
12,00	.472	± 0,22	± .009		

NESSUNA  
TOLLERANZA  
INDICATA

NO  
TOLERANCE  
PROVIDED



# ISO 3601-1

ORINGONE COMPLETE VERSION

March 2020 release

CROSS SECTION		ORINGONE TOLERANCE APPLIED		STANDARD TOLERANCE	
mm	Inch	mm	Inch	mm	Inch
12,70	.499	± 0,23	± .009		
13,00	.512	± 0,23	± .009		
14,00	.551	± 0,25	± .010		
14,40	.566	± 0,26	± .010		
15,00	.591	± 0,27	± .011		
16,00	.630	± 0,28	± .011		
17,00	.669	± 0,30	± .012		
18,00	.709	± 0,32	± .013	NESSUNA TOLLERANZA INDICATA	
19,00	.747	± 0,34	± .013		
19,20	.756	± 0,34	± .013		
20,00	.787	± 0,36	± .014		
21,00	.827	± 0,37	± .015		
22,00	.865	± 0,38	± .015		
24,00	.944	± 0,42	± .017		
25,00	.983	± 0,43	± .017		
25,86	1.018	± 0,44	± .017	NO TOLERANCE PROVIDED	
26,00	1.022	± 0,44	± .017		
28,00	1.100	± 0,49	± .019		
30,00	1.179	± 0,54	± .021		
32,00	1.260	± 0,54	± .021		
35,00	1.378	± 0,54	± .021		
40,00	1.572	± 0,72	± .028		
60,00	2.362	± 1,08	± .043		

