

## EZTRA® 012

Endless O-Rings Perfluoroelastomers  
REV. 02

### General Application

#### Temperature Range

From -5°C  
To 260°C

#### Color

Black

#### Application Target

Chemical Aggressivity

#### Compliances

NORSOK M-710 Ed 3  
API6A  
NACE TM0187

#### Note

#### Disclaimer

Tests performed on test slabs. Temperatures, applications and indications are meant as basic suggestions and valid for static applications with no other specific media and or conditions.

### PHYSICAL AND MECHANICAL PROPERTIES

Property	Test STD	Unit	Value
Density	ISO 2781	g/cm <sup>3</sup>	1,95 ± 0,03
Hardness	D2240	ShA	90 ± 5
Tensile Strength	D1414	N/mm <sup>2</sup>	>16
Elongation	D1414	%	>156
Tear resistance		N/mm	
TR 10	ASTM D1329	°C	
Brittle Point		°C	
C. Set 70h @200°C	ASTM D395	%	<20
C. Set 70h @250°C	ISO 815	%	

### AGEING PROPERTIES

Environment	Test STD	Unit	Value
	<i>Hardness Change</i>	ShA	
	<i>Tensile Strength</i>	%	
	<i>Elongation</i>	%	
	<i>Volume</i>	%	
	<i>Weight</i>	%	
	<i>Hardness Change</i>	ShA	
	<i>Tensile Strength</i>	%	
	<i>Elongation</i>	%	
	<i>Volume</i>	%	
	<i>Weight</i>	%	
	<i>Hardness Change</i>	ShA	
	<i>Tensile Strength</i>	%	
	<i>Elongation</i>	%	
	<i>Volume</i>	%	
	<i>Weight</i>	%	
	<i>Hardness Change</i>	ShA	
	<i>Tensile Strength</i>	%	
	<i>Elongation</i>	%	
	<i>Volume</i>	%	
	<i>Weight</i>	%	

