

EZTRA® 012

Endless O-Rings Perfluoroelastomers
REV. 01

General Application

Temperature Range

From -5°C
To 260°C

Color

Black

Application Target

Chemical Aggressivity

Compliances

NORSOK M-710 Ed 3
API6A
NACE TM0187

Composition – IMDS Data

CAS n°	Qty %

Note

Disclaimer

Tests performed on test slabs. Temperatures, applications and indications are meant as basic suggestions and valid for static applications with no other specific media and or conditions.

PHYSICAL AND MECHANICAL PROPERTIES

Property	Test STD	Unit	Value
Density	ISO 2781	g/cm ³	1,95 ± 0,03
Hardness	ISO 7619-1	ShA	90 ± 5
Tensile Strength	ISO 37	N/mm ²	>14,8
Elongation	ISO 37	%	>156
Tear resistance		N/mm	
TR 10	ASTM D1329	°C	
Brittle Point		°C	
C. Set 70h @200°C	ASTM D395	%	<21
C. Set 70h @300°C	ASTM D395	%	

AGEING PROPERTIES

Environment	Test STD	Unit	Value
	<i>Hardness Change</i>	ShA	
	<i>Tensile Strength</i>	%	
	<i>Elongation</i>	%	
	<i>Volume</i>	%	
	<i>Weight</i>	%	
	<i>Hardness Change</i>	ShA	
	<i>Tensile Strength</i>	%	
	<i>Elongation</i>	%	
	<i>Volume</i>	%	
	<i>Weight</i>	%	
	<i>Hardness Change</i>	ShA	
	<i>Tensile Strength</i>	%	
	<i>Elongation</i>	%	
	<i>Volume</i>	%	
	<i>Weight</i>	%	
	<i>Hardness Change</i>	ShA	
	<i>Tensile Strength</i>	%	
	<i>Elongation</i>	%	
	<i>Volume</i>	%	
	<i>Weight</i>	%	

