

# Z219

## FKM 75 BROWN

### RAL 8028

Update 26 March 2019

#### General Application

#### Temperature Range

From -20°C  
To 220°C

#### General Environmental Application

Chemicals  
Hydrocarbons  
High Temperatures  
---  
---

#### Compliances

#### Composition – IMDS Data

CAS n°	Qty %

#### Note

...

#### Disclaimer

Temperatures, applications and indications here above are meant as basic suggestions and valid for static applications with no other specific media and or conditions.

#### PHYSICAL AND MECHANICAL PROPERTIES

Property	Test STD	Unit	Value
Density	ASTM D297	g/cm <sup>3</sup>	2,12 ± 0,03
Hardness	ASTM D2240	ShA	75 ±5
Tensile Strength	ASTM D412C	N/mm <sup>2</sup>	12,5
Elongation	ASTM D412C	%	182
Tear resistance	ASTM D624B	N/mm	19
TR 10	ASTM D1329	°C	-17
Brittle Point		°C	
C. Set 24h @200°C		%	
C. Set 70h @200°C		%	

#### AGEING PROPERTIES

Environment	Test STD	Unit	Value
Air 70h @200°C	<i>Hardness Change</i>	ShA	
	<i>Tensile Strength</i>	%	
	<i>Elongation</i>	%	
	<i>Volume</i>	%	
	<i>Weight</i>	%	
Air 70h @250°C	<i>Hardness Change</i>	ShA	
	<i>Tensile Strength</i>	%	
	<i>Elongation</i>	%	
	<i>Volume</i>	%	
	<i>Weight</i>	%	
Oil ASTM 3 70h @150°C	<i>Hardness Change</i>	ShA	
	<i>Tensile Strength</i>	%	
	<i>Elongation</i>	%	
	<i>Volume</i>	%	
	<i>Weight</i>	%	
Fuel ASTM C 70h @23°C	<i>Hardness Change</i>	ShA	
	<i>Tensile Strength</i>	%	
	<i>Elongation</i>	%	
	<i>Volume</i>	%	
	<i>Weight</i>	%	

